





# Turnstiles Full Height BA3



## COMFORT OF PASSAGE

FIRSTLY



## INTUITIVE

CONFIGURATION

### DEVICE DESCRIPTION

Single, full height turnstile. The three sections of the rotor arms allow for comfortable passage. The device designed to assist pedestrian access control at guarded passage ways.

#### Examples of use:

- points of ticket control and access control for passenger traffic,
- airports/seaports,
- passages for authorised personnel, directing passenger traffic,
- points of access control in secured buildings (e.g. state offices such as border crossing points, other services),
- points of ticket control and fees at museums, theatres, cinemas, exhibitions, fair areas, show facilities, paid toilets, points of ticket control at sports facilities, e.g. swimming pools, stadiums, other sports and show facilities,
- access and time attendance control points in working places, e.g. offices, dedicated areas in factories.






**VERSATILITY OF USE**  
SITE-SPECIFIC FOR EACH FACILITY


## DEVICE DESCRIPTION



## FINISH OPTIONS






### RAL COLOR PALETTE EXAMPLES



Standard finish  
 Non-standard colour/non-standard finishing

## FUNCTIONS



### 1. NEW ELECTRONIC SYSTEM

The display allows you to change the configuration by setting in the program MENU. Readable MENU along with the possibility of changing many parameters of the device.

### 2. LED PICTOGRAMS

Visual information identifies unlocking or locking status of the device arms' movement. Green arrow indicates that the mechanism locking system is unlocked. Red cross indicates that the mechanism locking system is locked.

### 3. ENTRY AND EXIT CONTROL

The device's mechanism is equipped with a system supporting pedestrian traffic control in both traffic directions (entry/exit from the control zone).

### 4. BACKWARD MOTION LOCKING

Locking the backward motion disables the arms rotation in the direction opposite to the one defined by the external controlling device. The blockade is to make it difficult to pass 2 people on the basis of a single authorization signal for the transition from an external device.

### 5. ARM MOTION BOOSTER

The mechanism of the device is equipped with an electromechanical system supporting the rotary movement of the arms. This system, after applying force to the rotor's arm (thrust), switches on the engine, which helps rotate the rotor to the starting position.

## TECHNICAL PARAMETERS

### MECHANISM BA3

- System of locks for both directions of pedestrian traffic.
- Locking the backward motion.
- Unlocking the locking system in case of voltage decay.
- Electromechanical support for rotor positioning.
- Anti-collision system.

### ELECTRONIC SYSTEM

- Steering input for the first direction (e.g. for connecting a card reader and control button).
- Steering input for the second direction (e.g. for connecting a card reader and control button).
- 1 x feedback signal informing about the arms' rotation being done (Normal Closed or Normal Open).
- 1 x input to calibrate the arms' position.
- 1 x input to program the processor.

### TECHNICAL SPECIFICATIONS

| PARAMETER                     | VALUE                          |
|-------------------------------|--------------------------------|
| Power supply voltage:         | -24VAC                         |
| Maximum power consumption:    | 130 VA                         |
| Minimum current:              | 5 A                            |
| Control signal (adjustable):  | (max. 1 sec)                   |
| Feedback signal (adjustable): | 0V NO/NC                       |
| Operating temperature:        | -25° to +50° C [-13° to 122°F] |
| Storage temperature:          | -30° to +60° C [-22° to 140°F] |
| IP Code:                      | IP 43*                         |
| Max operating humidity:       | 10-80%                         |

\* it is possible to increase the degree of IP protection at the stage of ordering

### DEVICE NAMING SCHEME

| Marking description | Series | Number of lanes | Number of rotor wings | Finish type |      |       |
|---------------------|--------|-----------------|-----------------------|-------------|------|-------|
|                     |        |                 |                       | Body        | Roof | Rotor |
| Example             | BA3    | 1               | 3                     | N           | N    | N     |

### Examples of markings:


- BA3-1-3 NNN - BA3 series, number of lanes - 1, number of rotor wings - 3, finish type: stainless rotor, stainless body, stainless roof.

### Available finishes:

- N - stainless
- M - powder-coated
- O - galvanized
- D (duplex) - galvanized and powder-coated

**NOTE:** Standard finish includes AISI 304 (INOX) stainless steel.

# DIMENSIONS



**KEY:**

- External control signal - S/UTP cable
- 24 V supply - ØMY wire 3x1.5mm
- Foundation